

Merlin Utility Control



Key Features

- Automatic Control of the gas supply
- Clear LED status display
- Built-in connectivity to existing BAS and fire alarms
- Additional external gas detection sensors available.
- Key lock for authorization control
- Remote EPO buttons


Overview

The Merlin 1000Si utility control panel gives the user complete automatic control over the gas supply within the room whilst providing a convenient connection centre for additional systems. Utilizing a solenoid valve, the Merlin 1000Si provides a keyed authority over the incoming gas supply. The emergency knock off button is shrouded to ensure no accidental shutdowns occur. All the Merlin utility controls come with clearly labelled PCB boards to ensure easy installation. Additional gas sensors can be wired to the unit for extra safety. The Merlin range of utility controls can accept either a Nat

gas, CO or LPG sensor along with an input from the Merlin CO2 monitor. Built in connectivity to existing BAS systems and inputs for existing fire alarms make the unit perfect for renovation projects as well as new build. Dip switches on the reverse side of the facia panel allow for on-site adjustments on how the unit communicates with the buildings BMS / BAS system and the time-out function. The included time-out function can be adjusted between 2hrs, 4hrs and 8hrs or even disabled. The BMS / BAS relay output can be configured to signal "Gas ON", "GAS OFF" or "In Alarm".

Application

- K-12 and Higher Ed Science Classrooms.
- Designed to meet NSTA guidelines.
- Isolation of the gas supply in the event of high CO or CO2 concentrations.
- Decorative gas powered fire pits.
- Gas BBQ's installations.
- Commercial industrial spaces.
- Automatic isolation of the gas supply upon EM stop or gas detection.



Merlin Utility Control



Technical Specifications

Power supply – 100/240vac 50/60Hz

Protection – Overvoltage, overcurrent, surge protection (3amp)

Enclosure – Wall mounted Fully UL certified enclosure. *Flush Mount kit available.

Dimensions – W255 x H180 x D77 mm

Gas Solenoid Control Signal Output – 100/240VAC 50/60Hz

BAS Output - N/c, Com, N/o Max 1A @ 120vac

EM Stop Input – Volt Free*

Fan Switch Output – Volt Free*

Sensor Power Output – 24VDC
Sensor Signal Input – Volt Free*

CO² Monitor Signal Input – Volt Free*

Adjustable Time-out period – 2hr, 4hr or 8hr or disabled

Adjustable BAS Signal Output – Alarm “on” or Gas “on” / Gas “off”

*Volt Free. Do Not connect any device which generates a separate source of voltage on this circuit. Any voltage applied to these connections will damage the microcontroller.



1. Mains Supply Input, Single phase 100/240VAC 50/60Hz
2. Gas Solenoid Valve Power Output, Single phase 100/240VAC 50/60Hz
3. BAS Output Contacts. Common, Normally Closed and Normally Open.
4. Not Applicable
5. Remote Emergency Stop Button and Fire Alarm input (wired in series) Volt Free
6. Gas Detector (Nat Gas, CO, LPG or NOX) power supply and returned signal.
7. Fan Switch Output (purchased separately) see Fan Switch User Manual for Wiring Diagram.
8. CO² Monitor Signal Return
9. Not Applicable