

## Boiler Room Safety Solution


Gas Detection System Incorporating Built-in Connectivity to BMS and Fire Alarm systems with utility isolation. Remote EPO button controls electrical contactors.

AGS manufacture safety systems that meet and exceed the most rigorous standards for gas detection and isolation. This solution is ideal for boiler rooms that requires gas detection and utility isolation with the addition of controlling the electrics within the room.

The Merlin GDP2 provides management control over the connected utilities, remote emergency shut-off buttons, boiler heat detectors & fire alarms. Relay outputs can be used to advise the building management that an emergency has occurred or be used to communicate directly with the BMS / BAS.

The Merlin GDP2 can accept up to 6 gas detectors, the most common types in a boiler room application are natural gas, carbon monoxide or lpg. The system can also be equipped with additional audible alarm beacons which activate in the event of an emergency i.e. gas detected.

Below is example of our boiler room solution for projects which require gas detection & utility isolation. For further information please contact American Gas Safety or your local representative.



### Gas Safety Systems

### Utility Control

American Gas Safety, LLC. 4500 140<sup>th</sup> Ave N. Suite 101. Clearwater, FL 33672 T.(727) 608-4375 F.(727) 538-4237 [www.americangassafety.com](http://www.americangassafety.com)