

AGS **MINI MERLIN**

PROTECT LIFE & **BUILDING**

COMBINED NATURAL GAS & CARBON MONOXIDE MONITOR



ALARM LEVEL THRESHOLDS

AGSCH4CO-35 GOOD PRE ALARM ALARM

AGSCH4CO-50 GOOD PRE ALARM ALARM

AGSCH4CO-TWA GOOD PRE ALARM ALARM



NG: <8% LEL

NG: >8% LEL

NG: <10% LEL

NG: <8% LEL

NG: >8% LEL

NG: <10% LEL

PROVIDING SAFETY & CONTROLS IN

 SCIENCE LABORATORIES
BOILER ROOMS GAS FEATURES COMMERCIAL KITCHENS
PARKING GARAGES
EMS STATIONS

000





Plug & Play

Pre-programmed inputs & outputs for fast and easy installation

reset after an alarm state

Automatic Emergency

Boiler and/or gas supply

detected, emergency panic & fire alarm activation

Manual Reset Touch button for manual

or upon start-up

shutdown in alarm i.e. gas

Shutdown



Requirements Carbon monoxide interlock code in Texas, Florida & Georgia

.

with touch sensitive

Modern Design

Slim robust enclosure button

EARS OF

(PERIENCE

BMS & Fire Panel

Connectivity Outputs available to BMS systems via the controllers dry contacts

UL 61010 Listed Controlled



•

Easy To Use

UL 2075 Sensor

UL Listed

Clear TFT sreen displays status indications & live aas detector values

AUTOMATIC SHUTDOWN

0.0

0

The Mini Merlin is designed to shut off the source of a carbon monoxide or combustible gas leak via gas valve shut down, boiler safety circuits, or an electrical contactor.



FIND OUT MORE

info@americangassafety.com (727) - 608 - 4375

CO: 0-19ppm /

CO: >35ppm /


CO: 0-19ppm /

CO: 25-49ppm /

CO: 25-34ppm /

6304 Benjamin Road, Suite 502, Tampa, FL





@american-gas-safety