

AGSPBKL Datasheet

Emergency Shut Off Push Button With Keyed Reset





Product Overview

The AGSPBKL, multipurpose push button to be used for a wide range of applications, most commonly used with the AGS Merlin range of gas safety systems.

The AGSPBKL is a remote mounted push-to-break contact/key to-reset emergency push button.

It has a plastic wall mounting box, screw fix to flat surface. Connect electrical supply through single pole switch block via screw terminals.

Key Features

- ✓ Protects against vandalism, accidental damage, dust and grime
- ✓ Indoor use only
- Key-Lock Reset

Construction

- ✓ UL Listed to U.S. and Canadian safety standards.
- ✓ Contacts: 10a 500v max single pole
- √ Temperature range: 25°c to + 70°c protection: IP40

Installation

- 1. Separate switch base and top
- 2. Mount using the base as a template for holes
- ${f 3.}$ Knock out hole at top or bottom of base to allow cable entry
- 4. Feed cable through a cable gland and hole
- 5. Make necessary electrical connections
- 6. Replace switch top

Note: Key is captive on key reset models when the switch is in the unlatched position $% \left(1\right) =\left(1\right) \left(1\right) \left($

Dimensions



3.15" (H) x 2.87" (W) x 1.97" (D)

Find out more

American Gas Safety LLC

www.americangassafety.com

Head office

6304 Benjamin Road, Suite 502, Tampa, FL 33634

Tel: (727) 608-4375

Email: info@americangassafety.com

