

AGSPBTW Datasheet

Emergency Shut Off Push Button With Twist-Reset





Product Overview

The AGSPBTW, multipurpose push button to be used for a wide range of applications, most commonly used with the AGS Merlin range of gas safety systems.

The AGSPBTW is a remote mounted push-to-break contact, twist-to-reset emergency push button. It has a plastic wall mounting box, screw fix to flat surface. Connect electrical supply through single pole switch block via screw terminals.

Key Features

Protects against vandalism, accidental damage, dust and grime

- Indoor use only
 - Twist Release Reset

Construction

- UL Listed to U.S. and Canadian safety standards.
- Contacts: 10a 500v max single pole
- ✓ Temperature range: 25⁰c to + 70⁰c protection: IP40

Installation

- 1. Separate switch base and top
- 2. Mount using the base as a template for holes
- 3. Knock out hole at top or bottom of base to allow cable entry
- 4. Feed cable through a cable gland and hole
- 5. Make necessary electrical connections
- 6. Replace switch top

Note: Key is captive on key reset models when the switch is in the unlatched position $% \left({{{\rm{D}}_{\rm{B}}}} \right)$

Dimensions



3.15" (H) x 2.87" (W) x 1.97" (D)

Find out more

American Gas Safety LLC

www.americangassafety.com

Head office: 6304 Benjamin Road, Suite 502, Tampa, FL 33634

Tel: (727) 608-4375 Email: info@americangassafety.com