



# AGS1000Si Datasheet

## Single Output Utility Controller



**UL 61010 Listed  
 Controller**



**Clear LEDs Display  
 System Indications**



**Keyed ON/OFF  
 Authority Over  
 Utilities**



**BMS & Fire Panel  
 Connectivity**



**QR Code For  
 Quick Access  
 To Product  
 Information**



**Automatic Emergency  
 Utility Shutdown In  
 Alarm**



**Front Mounted  
 Panic Button For  
 Quick Shutdown**



**Automatic Time-Out  
 Feature (Disabled, 2, 4  
 or 8 hours)**

## Product Overview


The UL 61010 listed Merlin 1000Si Laboratory Utility Controller has been designed specifically for use in School and University Laboratories. The Merlin 1000Si is designed to give the teacher full control over the incoming gas supply with the lockable key-switch operation. In built connectivity allows for connection to existing fire alarm and building management systems and with its easy to use system status panel and labeled PCB the Merlin 1000Si is easy to install and to operate.

The Merlin 1000Si can work in conjunction with carbon dioxide, natural gas, carbon monoxide and LPG sensors. The Merlin 1000Si also has a built in "timeout" facility which will automatically shut off the gas solenoid valve at the end of a specific time period, this time period can be adjusted to 2, 4, 8 hours or can be overridden if required.

### Popular Applications:

- ✓ K-12 and Higher Education Science Classrooms
- ✓ Automatic Isolation Of Gas Supply Upon Gas Detection, Fire Alarm or Emergency Panic Button Activation
- ✓ Designed to meet NSTA guidelines & ICC Code.
- ✓ Keyed Utility Control with Emergency Shutdown


**FLUSH  
 MOUNT KIT  
 AVAILABLE**



## Product Specifications

Model:	Merlin 1000Si
Visual Indication	LED
Mains Electrical Power Input	110-120VAC
Gas Valve Output	110-120VAC
Current Consumption	12W max (50mA) @ 120VAC
Internal Fuse	3.15A
Gas Valve Output	3.15A
Operating Temperature	32 - 104°F 0-95%RH Non-Condensing
Audible Alarm Buzzer dB	65 dB (300mm distance in quiet conditions)
Housing Material	Polylac PA-765 Flame Retardant
Flame Rating	UL 94
UL Approval Reference	UL 61010-1 E464760
O/All Dimensions (H x W x D) inch	7.08 x 10 x 3.03"
Language:	English

## Merlin 1000Si Wiring Example



Find out more

**American Gas Safety LLC**

[www.americangassafety.com](http://www.americangassafety.com)

Head office:

6304 Benjamin Road, Suite 502, Tampa, FL 33634

Tel: (727) 608-4375

Email: [info@americangassafety.com](mailto:info@americangassafety.com)

