

# AGSENCFM Datasheet

# Flush Mount Solenoid Valve Enclosures





## **Product Overview**

Designed for general purpose indoor commercial use to enclose mechanical valves such as solenoid valves & ball valves. The hinged cover with latch provides easy access during installation and maintenance.

#### **Standards**





- Three piece assembly consisting of a base, wrapped and door.
- Components are attached and secured with metal screws.
- 14 gauge reverse formed base provides clearance for mounting hardware.
- Punched for left or right hinging of the door and ease of assembly.
- Wrapper is formed from 16 gauge steel, with no knock-outs in the sides.
- Flush mounting door assembly formed from 16 gauge steel.
- Door is fastened with a slotted quarter turn latch,
- A bonding stud is provided on the door and a grounding screw is provided in the enclosure.

#### **Finish**

Base, wrapped and door are finished in ANSI 61 gray powder coating


#### Installation

Step 1: Base, wrapped and door are finished in ANSI 61 gray powder coating

Step 2: Drill four (or six) .312inch diameter holes in mounting surface. Use

enclosure as the template to determine number of holes required and drilling locations.

<u>Step 3:</u> Fasten flush mount enclosure to mounting surface using M6 screws, flat washers, and hex nuts as shown.



### Sizes Available

Part Code	Height ± .25 (inches)	Width ± .25 (inches)	Depth ± .25 (inches)
AGSENC12126FM	12	12	6
AGSENC16126FM	16	12	6
AGSENC20166FM	20	16	6
AGSENC20206FM	20	20	6
AGSENC24208FM	24	20	8
AGSENC24248FM	24	24	8
AGSENC30248FM	30	24	8

#### Find out more

#### American Gas Safety LLC

www.americangassafety.com

Head office: 6304 Benjamin Road, Suite 502, Tampa, FL 33634



Tel: (727) 608-4375 Email: info@americangassafety.com