

AGSSOLVLV Datasheet

2-Way, Internally Piloted Normally Closed, 120Vac, 1/2" - 1 1/2" NPT







120Vac Power Input



UL Listed



Normally Closed Safety Shutoff



1/2" to 1 1/2" NPT Available For This Model Various Other Sizes Also Available

Standards





Product Overview

AGS water solenoid valves are normally closed (N/C) and constructed with a durable brass body, two-way inlet and outlet ports.

Sizes Available

Valve Size " (inch) NPT	AGS Part Number
1/2"	AGSSOLVLV12
3/4"	AGSSOLVLV34
1"	AGSSOLVLV1
1+1/4"	AGSSOLVLV114
1+1/2"	AGSSOLVLV112

Electrical Specifications

Rating	Nema 4
Holding VA	25
Inrush VA	14.0

Materials of Construction

Body	Lead Free Brass
Armature Tube	Stainless Steel 300
Fixed Core	Stainless Steel 400
Plunger	Stainless Steel 400
Spring	Stainless Steel 300
Shading Ring	Copper
Orifice	Lead Free Brass




Technical Specifications

	SOLVLV12	SOLVLV34	SOLVLV1	SOLVLV114	SOLVLV112
Pipe Size (Inch)	1/2"	3/4"	1"	1 1/4"	1 1/2"
Orifice Size (Inch)	1/2""	3/4"	1"	1 1/4"	1 1/2"
Flow Factor (CV)	4.80	9.80	14.00	28.00	36.00
Voltage (AC)	120VAC	120VAC	120VAC	120VAC	120VAC
Wattage (W)	8 Watts				
Pressure (PSI)	2-230 psi	2-230 psi	2-230 psi	2-150psi	2-150 psi
Sealing Material	EPDM/NSF	EPDM/NSF	EPDM/NSF	FKM	FKM
Temperature Range	14-280°F	14-280°F	14-280°F	14-280°F	14-280°F
Connector Supplied	Cable Grip DIN				
Medium Examples	Potable Water				

Valve Dimensions

	SOLVLV12	SOLVLV34	SOLVLV1	SOLVLV114	SOLVLV112
Valve Width (A):	1 9/16"	2 9/16"	2 9/16"	3 7/8"	3 7/8"
Valve Length (B):	2 19/32"	4 3/32"	4 3/4"	5 21/32"	5 21/32"
Valve Height (C):	3 3/16"	4 1/8"	4 13/32"	4 5/16"	4 15/16"
Coil Width (D):	1 3/16"	1 3/16"	1 3/16"	1 3/16"	1 3/16"
Coil Length (E):	1 21/32"	1 21/32"	1 21/32"	1 21/32"	1 21/32"
Coil Height (F):	2 1/8"	2 1/8"	2 1/8"	2 1/8"	2 1/8"



Note: The valve pictured above is with a simple coil, which may or may not reflect the exact specifications of the this particular build.

Find out more

American Gas Safety LLC

www.americangassafety.com

Head office:

6304 Benjamin Road, Suite 502, Tampa, FL 33634

Tel: (727) 608-4375

Email: info@americangassafety.com

