

Gas Shutdown

Solutions For "Panic-Button" Activated Gas Shutdown Systems





Valve Overview

The AGS range of normally closed, electrically operated gas valves provide safety shut down and LP (Liquefied petroleum). Closed when de-energized, open when energized.

These valves are suitable for CSD-1 applications along with on/off control on water heaters, atmospheric boilers, roof top make up air units, power burners and commercial kitchen ranges.

Add manual re-set by incorporating an AGS control or panic button.

Valve Model Numbers

Valve Size " (inch) NPT	AGS Part Number 0-5PSI	
1/2"	AGS-GSV12	
3/4"	AGS-GSV34	
1"	AGS-GSV1	
1+1/4"	AGS-GSV114	
1+1/2"	AGS-GSV112	
2"	AGS-GSV2	
2+1/2"	AGS-GSV212	
3"	AGS-GSV3	

4" and 6" Available As GSV4 and GSV6; see spec sheet for details

Button Overview

The AGS-EGOTW, multipurpose push button to be used for a wide range of applications with the AGS Merlin range of gas safety systems.

The AGS-EGOTW is a twist re-set, flush mounted button and comes with a clear protective cover to provide accidental activations.

The buttons consist of a normally-closed electrical contact that opens upon button activation, de-energizing the solenoid valve.


Button Model Numbers

Valve Size " (inch) NPT	Label	5PSI
AGSEGOTW	EMERGENCY GAS OFF	
W AGSEGOTWWM	EMERGENCY GAS OFF	
AGSEPOTW	EMERGENCY POWER OFF	
W AGSEPOTWWM	EMERGENCY POWER OFF	
AGSEBOTW	EMERGENCY BOILER OFF	
W AGSEBOTWWM	EMERGENCY	BOILER OFF

W = Weather Proof Custom Labels Available Upon Request



Power LED Indicator



Find out more American Gas Safety LLC www.americangassafety.com

Mounting Position

Head office: 6304 Benjamin Road, Suite 502, Tampa, FL 33634

Tel: (727) 608-4375 Email: info@americangassafety.com