

AGSEN

Weather Proof Enclosure



Made In The USA



Lockable or Screw Down Door



Three Year Guarantee Against Normal Use Breakage



Soft Rounded Edges



Opaque Tinted Removable Door



UV Resistant



Draw-Down Latch



UL50, UL508A, IEC 60529

Product Overview

Non-metallic lockable polycarbonate enclosures to provide physical or environmental protection. Helps guard against vandalism both intentional and accidental. Provides protection from water, dirt dust and debris.

Technical Data

Material	Injection molded polycarbonate
Nema Type	1, 3R, 4, 4X, 12
Approvals	UL / ULC
Standards	UL50, UL508A, IEC 60529
Ingress Protection	IP66
Gasket	Pour-in-place
Temp Range	-40F to 248F
Flame Rating	UL94 5VA
Outdoor / Water Immersion Rating	(f1)

Recommendations

Valve Size " (inch) NPT	AGSEN Enclosure Size
1/2"	10 x 8 x 6" (Inches)
3/4"	10 x 8 x 6" (Inches)
1"	10 x 8 x 6" (Inches)
1+1/4"	16 x 14 x 9" (Inches)
1+1/2"	16 x 14 x 9" (Inches)
2"	16 x 14 x 9" (Inches)
2+1/2"	18 x 16 x 11" (Inches)
3"	18 x 16 x 11" (Inches)

Sizes Available

6 x 6 x 5" (Inches)
8 x 6 x 5" (Inches)
10 x 8 x 6" (Inches)
10 x 10 x 6" (Inches)
12 x 10 x 7" (Inches)
14 x 12 x 7" (Inches)
16 x 14 x 9" (Inches)
18 x 16 x 11" (Inches)

Find out more

American Gas Safety LLC

www.americangassafety.com

Head office:

6304 Benjamin Road, Suite 502, Tampa, FL 33634

Tel: (727) 608-4375

Email: info@americangassafety.com

