


Gas solenoid valves are AGS GSV series, UL 429 Listed Safety Shutoff.
Water solenoids are AGS SOLVLV series, NSF Listed UL Listed brass lead free.

Product Selection:

AGSSOLRACK - _ - _ - _



Valve Selection

Selection Codes:

Code	Medium	Size (NPT)
GV12	Gas	1/2"
GV34	Gas	3/4"
GV1	Gas	1"
GV114	Gas	1 1/4"
GV112	Gas	1 1/2"

Gas Valves are AGSGSV series 0-5PSI, Aluminum Body, UL 429,

Code	Medium	Size (NPT)
SV12	Water	1/2"
SV34	Water	3/4"
SV1	Water	1"
SV114	Water	1 1/4"
SV112	Water	1 1/2"
SV2	Water	2"

Water valves are AGS SOLVLV series, NSF Approved Brass Lead Free, Normally Closed, 120VAC,

Example Part Codes

AGSSOLRACK - GV34 - SV12 - SV1

Includes a 3/4" gas valve, 1/2" and 1" water solenoid valves, wye-strainers, and manual isolation valve.

AGSSOLRACK - GV1- SV1

Includes a 1" gas valve, 1" water valve, wye-strainers, and manual isolation valves.

Technical Information:

Gas Valves

CFH at Pressure Drop of 1-Inch Water Column.

Size	Pressure (PSI)	Capacity (CFH)	Capacity (BTU/hr)
1/2"	0-5	226	226,014
3/4"	0-5	523	522,657
1"	0-5	590	589,755
1+1/4"	0-5	1,360	1,369,615
1+1/2"	0-5	1,663	1,663,320
2"	0-5	2,355	2,355,488

Water Valves

Size	Pressure (PSI)	Temp Range (F)	Cv
1/2"	0.5-230	32-266	4.5
3/4"	0.5-230	32-266	7.6
1"	0.5-230	32-266	12
1+1/4"	0.5-230	32-266	22
1+1/2"	0.5-230	32-266	30
2"	0.5-230	32-266	48

Find out more

American Gas Safety LLC

www.americangassafety.com

Head office:

6304 Benjamin Road, Suite 502, Tampa, FL 33634

Tel: (727) 608-4375

Email: info@americangassafety.com

